SAFETY DATA SHEET

B51W620

Section 1. Identification

| Product name | : PrepRite® ProBlock® Interior/Exterior Latex Primer/Sealer White |
|--|--|
| Product code | : B51W620 |
| Other means of identification | : Not available. |
| Product type | : Liquid. |
| Relevant identified uses of t | he substance or mixture and uses advised against |
| Paint or paint related material. | |
| | |
| Manufacturer | : THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115 |
| Emergency telephone number of the company | : US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year |
| Product Information Telephone Number | : US / Canada: 1-800-474-3794 Mexico: Not Available |
| Regulatory Information Telephone Number | : US / Canada: (216) 566-2902 Mexico: Not Available |
| Transportation Emergency Telephone Number | : US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year |

Section 2. Hazards identification

| OSHA/HCS status | : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). |
|--|---|
| Classification of the substance or mixture | : CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 |
| GHS label elements Hazard pictograms | |
| Signal word | : Danger |
| Hazard statements | : Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure. (lungs) |
| Precautionary statements | |
| General | Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. |
| Prevention | : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. |

| Date of issue/Date | of revision | : 4/14/2021 | Date of previous issue | : 1/29/2021 | Version | : 20.04 | 1/12 |
|--------------------|--------------------------------|--------------------|------------------------|-------------|---------|-----------|------|
| B51W620 | PrepRite® ProBlock® I White | nterior/Exterior I | Latex Primer/Sealer | | SHW-85- | NA-GHS-US | |

Section 2. Hazards identification

| Response | : IF exposed or concerned: Get medical advice or attention. |
|-------------------------------------|---|
| Storage | : Store locked up. |
| Disposal | : Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental label elements | WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure. This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, |
| | lakes or ponds. See Environmental Data Sheet (EDS) for additional details. |
| | Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage. |
| Hazards not otherwise classified | : None known. |

Section 3. Composition/information on ingredients

| Substance/mixture | : Mixture |
|-------------------|------------------|
| Other means of | : Not available. |
| identification | |

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|------------------|-------------|------------|
| Titanium Dioxide | ≥10 - ≤25 | 13463-67-7 |
| Talc | ≤10 | 14807-96-6 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

| Eye contact | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. |
|--------------|---|
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Skin contact | Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse. |

Section 4. First aid measures

| Ingestion | : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
|-----------------------------|---|
| Most important symptoms/e | effects, acute and delayed |
| Potential acute health effe | <u>cts</u> |
| Eye contact | : No known significant effects or critical hazards. |
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : No known significant effects or critical hazards. |
| Ingestion | : No known significant effects or critical hazards. |
| Over-exposure signs/symp | <u>otoms</u> |
| Eye contact | : No specific data. |
| Inhalation | : No specific data. |
| Skin contact | : No specific data. |
| Ingestion | : No specific data. |
| Indication of immediate me | dical attention and special treatment needed, if necessary |
| Notes to physician | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : No specific treatment. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

See toxicological information (Section 11)

| Section 5. Fire-fighting measures | | | | |
|--|---|--|--|--|
| Extinguishing media | | | | |
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. | | | |
| Unsuitable extinguishing media | : None known. | | | |
| Specific hazards arising from the chemical | : In a fire or if heated, a pressure increase will occur and the container may burst. | | | |
| Hazardous thermal decomposition products | : Decomposition products may include the following materials: metal oxide/oxides | | | |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. | | | |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. | | | |

| Date of issue/Date | of revision | : 4/14/2021 | Date of previous issue | : 1/29/2021 | Version | : 20.04 | 3/12 |
|--------------------|------------------------------|-------------------|------------------------|-------------|---------|-----------|------|
| B51W620 | PrepRite® ProBlock® White | Interior/Exterior | Latex Primer/Sealer | | SHW-85- | NA-GHS-US | |

Section 6. Accidental release measures

| Personal precautions, protec | tive equipment and emergency procedures |
|--------------------------------|---|
| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders | : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| Environmental precautions | : This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details. |
| | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |
| Methods and materials for co | ntainment and cleaning up |
| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Large spill | : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |
| Section 7 Handlin | a and storage |

siorage ''y

| Precautions for safe handling | |
|--|---|
| Protective measures | Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |

: 1/29/2021

Section 7. Handling and storage

| Conditions for safe storage, | 1 | Store in accordance with local regulations. Store in original container protected from | | | | |
|------------------------------|---|---|--|--|--|--|
| including any | | direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials | | | | |
| incompatibilities | | see Section 10) and food and drink. Store locked up. Keep container tightly closed | | | | |
| | | and sealed until ready for use. Containers that have been opened must be carefully | | | | |
| | | resealed and kept upright to prevent leakage. Do not store in unlabeled containers. | | | | |
| | | Use appropriate containment to avoid environmental contamination. See Section 10 for | | | | |
| | | incompatible materials before handling or use. | | | | |

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

| Ingredient name | CAS # | Exposure limits |
|------------------|------------|--|
| Titanium Dioxide | 13463-67-7 | ACGIH TLV (United States, 3/2020). TWA: 10 mg/m ³ 8 hours. OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust |
| Talc | 14807-96-6 | NIOSH REL (United States, 10/2016). TWA: 2 mg/m³ 10 hours. Form: Respirable fraction ACGIH TLV (United States, 3/2020). TWA: 2 mg/m³ 8 hours. Form: Respirable fraction |

Occupational exposure limits (Canada)

| Ingredient name | CAS # | Exposure limits | | |
|---|------------|--|--|--|
| Titanium dioxide | 13463-67-7 | CA British Columbia Provincial (Canada, 1/2020). TWA: 10 mg/m³ 8 hours. Form: Total dust TWA: 3 mg/m³ 8 hours. Form: respirable fraction CA Quebec Provincial (Canada, 7/2019). TWAEV: 10 mg/m³ 8 hours. Form: Total dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 10 mg/m³ 8 hours. CA Ontario Provincial (Canada, 6/2019). TWA: 10 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2019). STEL: 20 mg/m³ 15 minutes. TWA: 10 mg/m³ 8 hours. | | |
| talc (none asbestiform) | 14807-96-6 | CA British Columbia Provincial (Canada, 1/2020). TWA: 2 mg/m³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours. Form: Respirable dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m³ 8 hours. Form: Respirable particulate CA Ontario Provincial (Canada, 6/2019). TWA: 2 mg/m³ 8 hours. Form: Respirable particulate CA Ontario Provincial (Canada, 6/2019). TWA: 2 mg/m³ 8 hours. Form: Respirable particulate CA Saskatchewan Provincial (Canada, 7/2013). | | |
| ate of issue/Date of revision : 4/14/202 51W620 PrepRite® ProBlock® Interior/Exte White | | : 1/29/2021 Version : 20.04 5/1. SHW-85-NA-GHS-US | | |

Section 8. Exposure controls/personal protection

| | | | | TWA: 2 mg/m ³ 8 hours. Form: respirable fraction | |
|----------------------------------|---------|---|--|---|--|
| Occupational exposure lim | nits (I | <u>Mexico)</u> | | | |
| | | | CAS # | Exposure limits | |
| None. | | | | | |
| Appropriate engineering controls | : | local exhaust ventilation | on or other engin | s, gas, vapor or mist, use process enclosures, eering controls to keep worker exposure to mmended or statutory limits. | |
| Environmental exposure controls | : | this product to enter | drains, sewers | New Use Rule (SNUR) Chemical. Do not allow , wastewater treatment systems, groundwater, nmental Data Sheet (EDS) for additional | |
| | | they comply with the r | equirements of e s, filters or engin | cess equipment should be checked to ensure nvironmental protection legislation. In some eering modifications to the process equipment to acceptable levels. | |
| Individual protection measured | ures | | | | |
| Hygiene measures | : | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. | | | |
| Eye/face protection | : | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. | | | |
| Skin protection | | | | | |
| Hand protection | : | worn at all times when necessary. Consideri during use that the glo noted that the time to glove manufacturers. | n handling chemic ng the parameter oves are still retain breakthrough for In the case of m | complying with an approved standard should be cal products if a risk assessment indicates this is rs specified by the glove manufacturer, check ning their protective properties. It should be any glove material may be different for different ixtures, consisting of several substances, the accurately estimated. | |
| Body protection | : | | | body should be selected based on the task being should be approved by a specialist before | |
| Other skin protection | : | | ng performed and | al skin protection measures should be selected d the risks involved and should be approved by a | |
| Respiratory protection | : | appropriate standard | or certification. F | exposure, select a respirator that meets the Respirators must be used according to a re proper fitting, training, and other important | |

: 1/29/2021

Section 9. Physical and chemical properties

| Appearance | |
|--|---|
| Physical state | : Liquid. |
| Color | : Not available. |
| Odor | : Not available. |
| Odor threshold | : Not available. |
| рН | : 8.8 |
| Melting point/freezing point | : Not available. |
| Boiling point/boiling range | : 100°C (212°F) |
| Flash point | : Closed cup: Not applicable. |
| Evaporation rate | : 0.09 (butyl acetate = 1) |
| Flammability (solid, gas) | : Not available. |
| Lower and upper explosive (flammable) limits | : Not available. |
| Vapor pressure | : 2.3 kPa (17.5 mm Hg) [at 20°C] |
| Vapor density | : 1 [Air = 1] |
| Relative density | : 1.31 |
| Solubility | : Not available. |
| Partition coefficient: n- octanol/water | : Not available. |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Viscosity | : Kinematic (40°C (104°F)): >0.205 cm ² /s (>20.5 cSt) |
| Molecular weight | : Not applicable. |
| Aerosol product | |
| Heat of combustion | : 0.503 kJ/g |

Section 10. Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|--|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : No specific data. |
| Incompatible materials | : No specific data. |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

7/12

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|----------------------|---------|-------|----------------------|-------------|
| Titanium Dioxide | Skin - Mild irritant | Human | - | 72 hours 300 ug l | - |
| Talc | Skin - Mild irritant | Human | - | 72 hours 300 ug I | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|--------------------------|------|---------|-----|
| Titanium Dioxide Talc | - | 2B 3 | - |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

| Name | ••• | Route of exposure | Target organs |
|------|------------|----------------------|---------------|
| Talc | Category 1 | inhalation | lungs |

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effects

- Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.
- Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristicsEye contact: No specific data.

| Date of issue/Date | of revision | : 4/14/2021 | Date of previous issue | : 1/29/2021 | Version | : 20.04 | 8/12 |
|--------------------|------------------------------|--------------------|------------------------|-------------|---------|-----------|------|
| B51W620 | PrepRite® ProBlock® In White | nterior/Exterior L | _atex Primer/Sealer | | SHW-85- | NA-GHS-US | |

Section 11. Toxicological information

| Inhalation | : No specific data. |
|--------------------------------|--|
| Skin contact | : No specific data. |
| Ingestion | : No specific data. |
| | |
| Delayed and immediate ef | fects and also chronic effects from short and long term exposure |
| Short term exposure | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Long term exposure | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Potential chronic health ef | fects |
| Not available. | |
| General | : Causes damage to organs through prolonged or repeated exposure. |
| Carcinogenicity | : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Teratogenicity | : No known significant effects or critical hazards. |
| Developmental effects | : No known significant effects or critical hazards. |
| Fertility effects | : No known significant effects or critical hazards. |
| - | |

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|---------------------------------------|------------------------------|----------|
| Titanium Dioxide | Acute LC50 >1000000 μg/l Marine water | Fish - Fundulus heteroclitus | 96 hours |

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

| Soil/water | partition |
|-------------|-----------|
| coefficient | (Koc) |

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

| Date of issue/Date | of revision | : 4/14/2021 | Date of previous issue | : 1/29/2021 | Version | : 20.04 | 9/12 |
|--------------------|------------------------------|--------------------|------------------------|-------------|---------|-----------|------|
| B51W620 | PrepRite® ProBlock® In White | nterior/Exterior I | Latex Primer/Sealer | | SHW-85- | NA-GHS-US | |

Section 13. Disposal considerations

Disposal methods

: This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | | - | - | - | - |
|-------------------------------|-----------------------|-----------------------|--------------------------|----------------|----------------|
| | DOT Classification | TDG Classification | Mexico Classification | ΙΑΤΑ | IMDG |
| UN number | Not regulated. | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - | - | - |
| Transport hazard class(es) | - | - | - | - | - |
| Packing group | - | - | - | - | - |
| Environmental hazards | No. | No. | No. | No. | No. |
| Additional information | - | - | - | - | - |

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according : Not available. to IMO instruments

Proper shipping name

: Not available.


| Date of issue | e/Date of revision | : 4/14/2021 | Date of previous issue | : 1/29/2021 | Version | : 20.04 | 10/12 |
|---------------|--------------------|------------------------|------------------------|-------------|----------|-----------|-------|
| B51W620 | • | k Interior/Exterio | r Latex Primer/Sealer | | SHW-85-N | IA-GHS-US | |
| | White | | | | | | |

Section 15. Regulatory information

| • | • |
|--|---|
| U.S. Federal regulations | : TSCA 5(a)2 final significant new use rules: Sodium Nitrite |
| | This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details. |
| <u>SARA 313</u> | |
| SARA 313 (40 CFR 372.45 |) supplier notification can be found on the Environmental Data Sheet. |
| California Prop. 65 WARNING: This product correproductive harm. | ontains chemicals known to the State of California to cause cancer and birth defects or other |
| International regulations | |
| International lists | Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. |

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Vietnam inventory: Not determined.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

| | Justification | |
|---|--|--|
| CARCINOGENICITY - Cat SPECIFIC TARGET ORGA | Calculation method Calculation method | |
| <u>History</u> | | |
| Date of printing | : 4/14/2021 | |
| Date of issue/Date of revision | : 4/14/2021 | |
| Date of previous issue | : 1/29/2021 | |
| Version | : 20.04 | |

| Date of issue/Date | of revision | : 4/14/2021 | Date of previous issue | : 1/29/2021 | Version | : 20.04 | 11/12 |
|--------------------|---------------------------|-------------------|------------------------|-------------|---------|-----------|-------|
| B51W620 | PrepRite® ProBlock® White | Interior/Exterior | Latex Primer/Sealer | | SHW-85- | NA-GHS-US | |

Section 16. Other information

| Key to abbreviations | : ATE = Acute Toxicity Estimate |
|----------------------|--|
| - | BCF = Bioconcentration Factor |
| | GHS = Globally Harmonized System of Classification and Labelling of Chemicals |
| | IATA = International Air Transport Association |
| | IBC = Intermediate Bulk Container |
| | IMDG = International Maritime Dangerous Goods |
| | LogPow = logarithm of the octanol/water partition coefficient |
| | MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 |
| | as modified by the Protocol of 1978. ("Marpol" = marine pollution) |
| | N/A = Not available |
| | SGG = Segregation Group |
| | UN = United Nations |
| | |

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.