

Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.	U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072
IDENTITY (As Used On Label and List) STRIP EZE LIQUID	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I	
Manufacturer's Name Cantol USA Inc.	Emergency Telephone Number (24 Hours, CHEMTREC):800-424-9300
Address (Number, Street, City, State, and Zip) 3800 Jasper St. Unit 1	Telephone Number for Information 888-422-6865
Philadelphia, PA 19124	Date Prepared January 1, 2011
www.cantol.com	Signature of Preparer (Optional) MSDS Committee

Section II - Hazardous Ingredients/Identity Information				
Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
*METHYLENE CHLORIDE (75-09-2)	25 PPM	50 PPM	NONE	77
1-METHYL-4-(1-METHYLETHENYL) CYCLOHEXENE (5989-27-5)	NONE	NONE	NONE	>1
*TOLUENE (108-88-3)	200 PPM	100 PPM	NONE	6
*METHANOL (67-56-1)	200 PPM	200 PPM	NONE	4
All chemicals marked with an asterisk () are subject to the reporting requirements of section 313 of Title III of the Super Fund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. This statement must remain a part of this Material Safety Data Sheet. Any copy or redistribution of this MSDS shall include this statement.				

Section III - Physical/Chemical Characteristics			
Boiling Point (°F)	102-230	Specific Gravity (H₂O = 1)	1.14
Vapor Pressure (mm Hg.)	NO DATA	Melting Point	N/A
Vapor Density (AIR = 1)	>1	Evaporation Rate (Butyl Acetate=1)	>1
Solubility in Water	Negligible	Appearance and Odor	Amber liquid with characteristic solvent odor.

Section IV - Fire and Explosion Hazard Data			
Flash Point (Method Used) None by TCC	Flammable Limits N/A	LEL	UEL
Extinguishing Media Foam, Carbon Dioxide, Dry Chemical, Water			
Special Fire Fighting Procedures High heat will produce hydrochloric acid. Firefighters should wear protective equipment against corrosive and harmful vapors.			
Unusual Fire and Explosion Hazards NONE			
NFPA: Health, 3; Flammability, 0; Reactivity, 0; SH - NONE			
HMIS: Health, 3; Flammability, 0; Reactivity, 0; PE - D			

STRIP EZE LIQUID

Section V - Reactivity Data			
Stability	Unstable		Conditions to Avoid Heat
	Stable	XX	
Incompatibility (Materials to Avoid) Strong alkalis, oxidizing materials			
Hazardous Decomposition or By-products Burning may yield hydrochloric acid, phosgene, carbon dioxide and carbon monoxide.			
Hazardous Polymerization	May Occur		Conditions to Avoid NONE
	Will Not Occur	XX	
Section VI - Health Hazard Data			
Route(s) of Entry:			
	Inhalation? YES	Skin? YES	Ingestion? YES
Health Hazards (Acute and Chronic) ACUTE: EYES: Causes severe burns. SKIN: Causes severe burns. INGESTION: Harmful if swallowed. INHALATION: Overexposure can cause headaches, dizziness and nausea. CHRONIC: Exposure to very high vapor concentrations may cause liver and kidney damage.			
Carcinogenicity			
	NTP? NO	IARC Monographs? NO	OSHA Regulated? NO
Methylene chloride is a possible human cancer hazard based on tests with laboratory animals. It has not been identified as a carcinogen or probable carcinogen by NTP, IARC or OSHA.			
Signs and Symptoms of Exposure EYES: Redness, burning, pain. SKIN: Burning, pain. INHALATION: Headache, nausea. INGESTION: Burning to digestive tract.			
Medical Conditions Generally Aggravated by Exposure Prolonged and repeated inhalation of vapors may effect the breathing of persons with asthma-like conditions; not likely to occur when used according to directions.			
Emergency and First Aid Procedures EYES: Flush with plenty of water for at least 15 minutes. Seek prompt medical attention. SKIN: Wash with soap and water. Call a Physician. INHALATION: Remove to fresh air.			
Section VII - Precautions for Safe Handling and Use			
Steps To Be Taken In Case Material Is Released or Spilled Ventilate area. Soak up spill with oil absorbent. Remove any residue with detergent solution.			
Waste Disposal Method Dispose of used absorbent in proper receptacle for trash. Dispose of unwanted liquid as hazardous waste in accordance with EPA-RCRA.			
Precautions To Be Taken In Handling and Storing Do not get in eyes, on skin, or clothing. Use with adequate ventilation. Avoid breathing vapor. Keep container closed. Do not heat. KEEP OUT OF THE REACH OF CHILDREN.			
Other Precautions For industrial and institutional use only. Read and follow all label directions and precautions. Do not mix with any other chemicals.			
Section VIII - Control Measures			
Respiratory Protection (Specify Type) None if used in a well ventilated area.			
Ventilation	Local Exhaust NONE	Special NONE	
	Mechanical (General) NONE	Other NONE	
Protective Gloves Rubber, Neoprene		Eye Protection Eye goggles	
Other Protective Clothing or Equipment As needed to protect skin from exposure			
Work/Hygienic Practices Wash thoroughly after handling.			

Cantol USA Inc. OSHA/MSDS